

T-1 GRINDING WHEELS - 6" to 14" ALUMINUM OXIDE



GENERAL PURPOSE AO GRINDING WHEELS

Available in four aluminum oxide grits for general purpose ferrous metal grinding. Other grits and hardness specifications upon request. These wheels can be used as harder bond bench grinding wheels. The listed maximum speeds are for non-reinforced wheels. Reinforcement can be added for higher speed ratings.

TYPE 1



Size	RPM	A16-S4B	A24-S4B	A36-S4B	A46-S4B	A60-S4B
6 x 1/2 x 1	6,048	918090	918099	918110	918113	918115
6 x 3/4 x 1	6,048	918145	918150	918155	918160	918165
6 x 1 x 1	6,048	918185	918215	918225	918230	918235
7 x 1/2 x 1	5,183	918251	918252	918253	918255	918256
7 x 3/4 x 1	5,183	918265	918270	918275	918277	918278
7 x 1 x 1	5,183	918280	918285	918290	918295	918300
8 x 1/2 x 1	4,538	918330	918332	918333	918339	918340
8 x 1 x 1	4,538	918405	918410	918415	918420	918425
10 x 1 x 1	3,629	918481	918486	918489	918492	918495
10 x 1 x 1 1/4	3,629	918483	918485	918491	918493	918496
10 x 1 1/4 x 1 1/4	3,629	918515	918518	918520	918525	918527
10 x 1 1/2 x 1 1/4	3,629	918535	918540	918545	918550	918555
10 x 2 x 1 1/4	3,629	918560	918565	918570	918571	918575
12 x 1 x 1 1/4	3,023	918584	918585	918590	918594	918593
12 x 1 1/2 x 1 1/4	3,023	918610	918615	918625	918627	918629
12 x 2 x 1 1/4	3,023	918636	918640	918641	918655	918656
14 x 2 x 1 1/4	2,592	918675	918680	918685	918690	918695

Bushings are available for 1/2", 5/8" and 1" grinder shafts. 14 x 1 1/2" wheels can be made upon request.



CAUTION
The wheels and speeds on this page are non-reinforced. They can be made with reinforcement for higher speed ratings within the ANSI B7.1 Standards. Inquiries will be quoted.